

**MADE
FROM
REAL**

**REGULAR CAB
SPECIFICATIONS | RHD**



**MY16 D-MAX ISUZU PICKUP SPECIFICATIONS
REGULAR CAB**

ISUZU
Delivers

MODEL	D-MAX TFR54	D-MAX TFR86	D-MAX TFR86	D-MAX TFS86
TRIM	STD RIDE	HR (A/C)	HR (A/C, A/BAG)	(A/C, A,BAG)
DRIVE CONFIGURATION	4X2	4X2	4X2	4X4
SMOD	M160TO9	M160TP1	M160TP2	M160TP4
Engine				
Displacement (cc)	2499	2499	2499	2499
No. of Cylinders	4	4	4	4
Compression Ratio	18.3:1	18.1:1	18.1:1	18.1:1
Bore x Stroke (mm)	95.4 x 87.4	95.4 x 87.4	95.4 x 87.4	95.4 x 87.4
No. of Valves	16	16	16	16
Power (kW) @ r/min	58 @ 3800	100 @ 3600	100 @ 3600	100 @ 3600
Torque (Nm) @ r/min	176 @ 1800	320 @ 1800-2800	320 @ 1800-2800	320 @ 1800-2800
Fuel System	Direct Injection	Common Rail Direct Injection	Common Rail Direct Injection	Common Rail Direct Injection
Turbocharger	Std	Std	Std	Std
Intercooler	N/A	Std	Std	Std
Fuel Consumption ^(#2)				
Combined Cycle (l/100km)	7.9	9.6	10.7	10.7
Combined CO ₂ Emissions (g/km)	206	199	217	217
Fuel Type/Recommended Grade	Diesel/Premium Grade	Diesel/Premium Grade	Diesel/Premium Grade	Diesel/Premium Grade
Transmission				
Transmission Type	5-Speed Manual	5-Speed Manual	5-Speed Manual	5-Speed Manual
4WD Rotary Switch Control - 2-Speed Transfer Case	N/A	N/A	N/A	Std
Low Range Ratio	N/A	N/A	N/A	2.482
Front Differential				
Shift on the Fly	N/A	N/A	N/A	Std
Axle Ratio: Final Drive	N/A	N/A	N/A	4.1
Rear Differential				
Limited Slip Differential	N/A	Std	Std	Std
Axle Ratio: Final Drive	4.555	3.909	3.909	4.1
Chassis Design				
Wheel Suspension Front	Coil Spring	Hi-Ride Coil Spring	Hi-Ride Coil Spring	Coil Spring
Wheel Suspension Rear	Leaf Spring	Leaf Spring Overslung	Leaf Spring Overslung	Leaf Spring Overslung
Shock Absorbers	Twin-Tube Gas Pressurised (Heavy Duty)	Twin-Tube Gas Pressurised (Heavy Duty)	Twin-Tube Gas Pressurised (Heavy Duty)	Twin-Tube Gas Pressurised (Heavy Duty)
Hi-Ride Suspension	N/A	Std	Std	N/A
Skid Plate Guard	Std	Std	Std	Std
Engine Sump Guard	N/A	Std	Std	Std
Transfer Case Guard	N/A	N/A	N/A	Std
Fuel Tank Guard	Std	Std	Std	Std
Wheel/Tyres				
Tyre Size	195/R15 (AT)	205 R16C (AT)	205 R16C (AT)	245/70 R16 (AT)
Wheel Type/Size	6.0J x 15" Steel	6.5J-33 x 16" Steel	6.5J-33 x 16" Steel	7.0J-33 x 16" Steel
Spare Wheel Size/ Type	6.0J x 15" Steel	6.5J-33 x 16" Steel	6.5J-33 x 16" Steel	6.5J-33 x 16" Steel
Turning Circle: Tyres (m)	12.7	12.7	12.7	12.7
Turning Circle: Body (m)	13.5	13.5	13.5	13.5
Dimensions				
Length (mm)	5218	5218	5218	5218
Width (mm)	1860	1860	1860	1860
Width incl. Mirrors (mm)	2132	2132	2132	2132
Height (mm)	1790	1790	1790	1790
Wheelbase (mm)	3095	3095	3095	3095
Track Front/Rear (mm)	1510 / 1510	1570 / 1570	1571 / 1570	1570 / 1570
Ground Clearance (mm)	225	225	225	224
Loadbox Length (mm)	2318	2318	2318	2318
Loadbox Width (mm)	1534	1534	1534	1534
Loadbox Depth (mm)	440	440	440	440
Mass/Capacity				
Gross Vehicle Mass (GVM) (kg)	2850	2850	2850	2850
Gross Combined Mass (GCM) (kg)	4450	4450	4450	4950
Tare Mass (kg)	1705	1705	1710	1820
Payload (kg)	1086	1086	1081	1071
Towing Capacity (kg): Unbraked Trailer ^(#1)	750	750	750	750

MODEL	D-MAX TFR54	D-MAX TFR86	D-MAX TFR86	D-MAX TFS86
TRIM	STD RIDE	HR (A/C)	HR (A/C, A/BAG)	(A/C, A,BAG)
DRIVE CONFIGURATION	4X2	4X2	4X2	4X4
SMOD	M160TO9	M160TP1	M160TP2	M160TP4
Mass/Capacity				
Towing Capacity/Towbar Rating (kg): Trailer with Overrun Brake ^(#1)	2100	2100	2100	2100
Fuel Tank Capacity (l)	80	80	80	80
Loadbox Features				
Tie-down brackets in loadbox for load restraint	4	4	4	4
Rope hooks on load box (Side and Rear)	12	12	12	12
Cab Protector - Black	Std	Std	Std	Std
Safety Features				
Side impact protection bars	Std	Std	Std	Std
Anti-lock brakes (ABS)	N/A	N/A	Std	Std
Electronic brake-force distribution (EBD)	N/A	N/A	Std	Std
Brake assist system (BAS)	N/A	N/A	Std	Std
Driver and front passenger airbags	N/A	N/A	Std	Std
Interior/Exterior Lighting				
Centre High Level Stop Lamp	Std	Std	Std	Std
Interior Courtesy Lights	Std	Std	Std	Std
Halogen Headlights	Multi-Reflector	Multi-Reflector	Multi-Reflector	Multi-Reflector
Headlamps "On" Warning Buzzer	Std	Std	Std	Std
Exterior Features				
Radiator Grille Colour	Material Grey	Material Grey	Material Grey	Material Grey
Body Colour Front Bumper	Std	Std	Std	Std
Rear Step bumper With Tow pack Provision	Std	Std	Std	Std
Exterior Door Handle Colour	Material Black	Material Black	Material Black	Material Black
Mudflaps	Std	Std	Std	Std
Folding Exterior Mirror Colour	Manual, Black	Manual, Black	Manual, Black	Manual, Black
Interior Features				
Power Assisted Steering	Std	Std	Std	Std
Gearknob Trim	Std	Std	Std	Std
Front Seat Configuration	Split Bench	Split Bench	Split Bench	Split Bench
Seat Trim	Vinyl	Vinyl	Vinyl	Vinyl
Floor Trim	Vinyl	Vinyl	Vinyl	Vinyl
Driver Footrest	Std	Std	Std	Std
Air Conditioner	N/A	Manual	Manual	Manual
Cabin Air Filter (Pollen)	Std	Std	Std	Std
Anti-Dazzle Rear-View Mirror	Std	Std	Std	Std
12-V Auxiliary Power Supply	1	1	1	1
Lockable Glove Box	Std	Std	Std	Std
Door Trim with Storage Pockets and Integrated Cupholders	Std	Std	Std	Std
Fuel Flap Remote	Std	Std	Std	Std
Side Windows, Tinted	Std	Std	Std	Std
Fixed Rear Window, Tinted with No Defogger	Std	Std	Std	Std
Infotainment				
No. of Speakers	2	2	2	2
Radio Ready for Models without Audio System	Std	Std	Std	Std
Options				
16" Steel Wheels & 205R16C Tyres (All Terrain)	N/A	Std	Std	Std
16" Alloy Wheels & 245/70 R16C Tyres (All Terrain)	N/A	N/A	N/A	N/A
15" Steel Wheels & 195/R15 Tyres (All Terrain)	Std	N/A	N/A	N/A
Non integrated CD/MP3 Player, AM/FM, clock, Bluetooth Audio Streaming/Phone , Full Size USB	Std	Std	Std	Std
Warranty				
Warranty	Available	Available	Available	Available
Anti-Corrosion Warranty	Available	Available	Available	Available
Disclaimer: Abridged specifications correct as at time of printing and may subsequently change. Please contact your nearest dealer to confirm any specification changes.				
Notes:				
(#1) Towing capacity subject to country specific regulations. The weight of the towing vehicle, including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer, must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 & GA2) must not be exceeded. (e.g.: if a 3.0L 4x4 Diesel is towing 2,100kg its maximum Vehicle mass is 2,850kg in order to be within GCM of 4,950kg). (#2) Fuel Economy & CO ₂ data as per ECE R101 regulation in Europe. Note that the actual fuel consumption will depend on many factors including the driver's driving habits, prevailing conditions and the vehicle's equipment, condition and use.				

**MADE
FROM
REAL**

**CREW CAB
SPECIFICATIONS | RHD**



**MY16 D-MAX ISUZU PICKUP SPECIFICATIONS
CREW CAB**

ISUZU
Delivers

MODEL	D-MAX TFR86 DELUXE HR (A/C, A/BAG)	D-MAX TFS86 BASE (A/C, A/BAG)	D-MAX TFS86 DELUXE (A/C, A/BAG)	D-MAX TFS85 LUXURY LS	D-MAX TFS85 LUXURY LS (A/T)
TRIM	DELUXE HR (A/C, A/BAG)	BASE (A/C, A/BAG)	DELUXE (A/C, A/BAG)	LUXURY LS	LUXURY LS (A/T)
DRIVE CONFIGURATION	4X2	4X4	4X4	4X4	4X4
SMOD	M160TP6	M160TP8	M160TQ1	M160TQ4	M160TQ5
Engine					
Displacement (cc)	2499	2499	2499	3000	3000
No. of Cylinders	4	4	4	4	4
Compression Ratio	18.1:1	18.1:1	18.1:1	17.5:1	17.5:1
Bore x Stroke (mm)	95.4 x 87.4	95.4 x 87.4	95.4 x 87.4	95.4 x 104.9	95.4 x 104.9
No. of Valves	16	16	16	16	16
Power (kW) @ r/min	100 @ 3600 320 @ 1800- 2800	100 @ 3600 320 @ 1800- 2800	100 @ 3600 320 @ 1800- 2800	120 @ 3200 380 @ 1800- 2200	120 @ 3200 380 @ 1800- 2200
Torque (Nm) @ r/min					
Fuel System	Common Rail Direct Injection	Common Rail Direct Injection	Common Rail Direct Injection	Common Rail Direct Injection	Common Rail Direct Injection
Turbocharger	Std	Std	Std	Std	Std
Intercooler	Std	Std	Std	Std	Std
Fuel Consumption ^(#2)					
Combined Cycle (l/100km)	7.7	7.9	7.9	7.9	7.9
Combined CO ₂ Emissions (g/km)	203	208	208	209	208
Fuel Type/Recommended Grade	Diesel/Premium Grade	Diesel/Premium Grade	Diesel/Premium Grade	Diesel/Premium Grade	Diesel/Premium Grade
Transmission					
Transmission Type	5-Speed Manual	5-Speed Manual	5-Speed Manual	5-Speed Manual	5-Speed Auto
4WD Rotary Switch Control - 2-Speed Transfer Case	N/A	Std	Std	Std	Std
Low Range Ratio	N/A	2,482	2,482	2,482	2,482
Front Differential					
Shift on the Fly	N/A	Std	Std	Std	Std
Axle Ratio: Final Drive	N/A	4,1	4,1	3,727	3,727
Rear Differential					
Limited Slip Differential	Std	Std	Std	Std	Std
Axle Ratio: Final Drive	3,909	4,1	4,1	3,727	3,727
Chassis Design					
Wheel Suspension Front	Hi-Ride Coil Spring	Coil Spring	Coil Spring	Coil Spring	Coil Spring
Wheel Suspension Rear	Leaf Spring Overslung	Leaf Spring Overslung	Leaf Spring Overslung	Leaf Spring Overslung	Leaf Spring Overslung
Shock Absorbers	Twin-tube Gas Pressurised (Heavy Duty)	Twin-tube Gas Pressurised (Heavy Duty)	Twin-tube Gas Pressurised (Heavy Duty)	Twin-Tube Gas Pressurised (Heavy Duty)	Twin-Tube Gas Pressurised (Heavy Duty)
Hi-Ride Suspension	Std	N/A	N/A	N/A	N/A
Skid Plate Guard	Std	Std	Std	Std	Std
Engine Sump Guard	Std	Std	Std	Std	Std
Transfer Case Guard	N/A	Std	Std	Std	Std
Fuel Tank Guard	Std	Std	Std	Std	Std
Wheel/Tyres					
Tyre Size	205 R16C (AT) 6.5J-33 x 16"	245/70 R16C (AT) 7.0J-33 x 16"	245/70 R16C (AT) 7.0J-33 x 16"	245/70 R16C (AT) 7.0J-33 x 16"	245/70 R16C (AT) 7.0J-33 x 16"
Wheel Type/Size	Steel 6.5J-33 x 16"	Steel 6.5J-33 x 16"	Alloy 6.5J-33 x 16"	Alloy 6.5J-33 x 16"	Alloy 6.5J-33 x 16"
Full Size Spare Wheel/Size	Steel 6.5J-33 x 16"	Steel 6.5J-33 x 16"	Steel 6.5J-33 x 16"	Steel 6.5J-33 x 16"	Steel 6.5J-33 x 16"
Turning Circle: Tyres (m)	12.7	12.7	12.7	12.7	12.7
Turning Circle: Body (m)	13.5	13.5	13.5	13.5	13.5
Dimensions					
Length (mm)	5294	5294	5294	5294	5294
Width (mm)	1860	1860	1860	1860	1860
Width incl mirrors (mm)	2132	2132	2132	2132	2132
Height (mm)	1790	1790	1790	1790	1790
Wheelbase (mm)	3095	3095	3095	3095	3095
Track Front/Rear (mm)	1570 / 1570	1570 / 1570	1570 / 1570	1570 / 1570	1570 / 1570
Ground Clearance (mm)	224	224	224	224	224
Loadbox Length (mm)	1483	1483	1483	1483	1483
Loadbox Width (mm)	1534	1534	1534	1534	1534
Loadbox Depth (mm)	465	465	465	465	465
Mass/Capacity					
Gross Vehicle Mass (GVM) (kg)	2850	2850	2950	3000	3000
Gross Combined Mass (GCM) (kg)	4450	4450	4950	5000	5000
Tare Mass (kg)	1810	1815	1905	1970	1990
Payload (kg)	981	976	986	971	951
Towing Capacity (kg): Unbraked Trailer ^(#1)	750	750	750	750	750
Towing Capacity/Towbar Rating (kg): Trailer with Overrun Brake ^(#1)	2100	2100	2100	2000	2000
Fuel Tank Capacity (l)	80	80	80	80	80

MODEL	D-MAX TFR86 DELUXE HR (A/C, A/BAG)	D-MAX TFS86 BASE (A/C, A/BAG)	D-MAX TFS86 DELUXE (A/C, A/BAG)	D-MAX TFS85 LUXURY LS	D-MAX TFS85 LUXURY LS (A/T)
TRIM	DELUXE HR (A/C, A/BAG)	BASE (A/C, A/BAG)	DELUXE (A/C, A/BAG)	LUXURY LS	LUXURY LS (A/T)
DRIVE CONFIGURATION	4X2	4X4	4X4	4X4	4X4
SMOD	M160TP6	M160TP8	M160TQ1	M160TQ4	M160TQ5
Safety Features					
Anti-Lock Brakes (ABS)	N/A	N/A	Std	Std	Std
Electronic Brake-Force Distribution (EBD)	N/A	N/A	Std	Std	Std
Brake Assist System (BAS)	N/A	N/A	Std	Std	Std
Side Impact Protection Bars	Std	Std	Std	Std	Std
Height Adjustable 3-Point Seatbelts	Std	Std	Std	Std	Std
Seatbelt - Rear Center (3-Point)	Std	Std	Std	Std	Std
Seatbelt Pre-Tensioners	Std	N/A	Std	Std	Std
Driver and Front Passenger Airbags	Std	Std	Std	Std	Std
Collapsible Steering Column	Std	N/A	Std	Std	Std
ISOFIX Child Seat Attachment	N/A	N/A	N/A	Std	Std
Security Features					
Remote controlled central locking	Std	Std	Std	Std	Std
Tailgate centre pull handle	Black	Black	Black	Chrome + Key Cylinder	Chrome + Key Cylinder
Interior / Exterior Lighting					
Centre High Level Stop Lamp	Std	Std	Std	Std	Std
Interior courtesy lights	Std	Std	Std	Std	Std
Front Fog Lights	Std	Std	Std	Std	Std
Headlights	Halogen Multi-Reflector	Halogen Multi-Reflector	Halogen Multi-Reflector	Projector with Multi-Reflector - DRL	Projector with Multi-Reflector - DRL
Headlamps "On" Warning Buzzer	Std	Std	Std	Std	Std
Rear LED Combination Tail-Lights	N/A	N/A	N/A	Std	Std
Exterior Features					
Radiator Grille Colour	Material Grey	Material Grey	Material Grey	Bright Chrome	Bright Chrome
Front Bumper Colour	Body Colour	Body Colour	Body Colour	Body Colour	Body Colour
Rear Step Bumper With Tow Pack Provision	Std	Std	Std	N/A	N/A
Rear Step Bumper With Rear Park Assist	N/A	N/A	N/A	Std	Std
Exterior Door Handle Colour	Black	Black	Black	Chrome	Chrome
Folding Exterior Mirror	Manual, Black	Manual, Black	Manual, Black	Power, Chrome	Power, Chrome
Side Steps (Running Board)	N/A	N/A	N/A	Std	Std
Mudflaps	Std	Std	Std	Std	Std
Interior Features					
Power Assisted Steering	Std	Std	Std	Std	Std
Overhead console with Map Light	N/A	N/A	N/A	Std	Std
Gearknob Trim	Urethane	Urethane	Urethane	Urethane & Decor Plate	Urethane & Decor Plate
Front Seat Configuration	2 x Bucket Base	2 x Bucket Base	2 x Bucket Base	2 x Bucket Deluxe	2 x Bucket Deluxe
Head Restraint Rear	Std	Std	Std	Std	Std
Seat Trim	Base Cloth	Base Cloth	Base Cloth	Luxury Cloth	Leather
Height Adjustable Driver Seat	N/A	N/A	N/A	Std	Std
Seat Map Pockets	N/A	N/A	N/A	Std	Std
Floor Trim	Carpet	Carpet	Carpet	Carpet	Carpet
Driver Footrest	Std	Std	Std	Std	Std
Air-conditioner with Cabin air filter (Pollen)	Manual	Manual	Manual	Auto	Auto
Rear Heater Duct	Std	Std	Std	Std	Std
12-V auxiliary power supply	1	1	1	1	1
Infotainment					
No. of Speakers	4	2	4	6	6
Radio ready for models without audio system	Std	Std	Std	N/A	N/A
2Din (flush), CD Player, AM/FM, Clock, Bluetooth* (Hands Free/Audio) , USB/AUX , i-Pod Music Function, RDS	N/A	N/A	N/A	Std	Std
Options					
Non integrated CD/MP3 Player, AM/FM, clock, Bluetooth Audio Streaming/Phone, Full Size USB	Std	Std	Std	N/A	N/A
Warranty					
Warranty	Available	Available	Available	Available	Available
Anti-corrosion Warranty	Available	Available	Available	Available	Available

Disclaimer: Abridged specifications correct as at time of printing and may subsequently change. Please contact your nearest dealer to confirm any specification changes.

Notes: (#1) Towing capacity subject to country specific regulations. The weight of the towing vehicle, including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer, must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 & GA2) must not be exceeded. (e.g.: if a 3.0L 4x4 Diesel is towing 2,100kg its maximum Vehicle mass is 2,850kg in order to be within GCM of 4,950kg)

(#2) Fuel Economy & CO₂ data as per ECE R101 regulation in Europe. Note that the actual fuel consumption will depend on many factors including the driver's driving habits, prevailing conditions and the vehicle's equipment, condition and use.